

AXIS S1132

Out-of-the box ready server for high-definition surveillance

AXIS Camera Station S1132 Recorder is an out-of-the-box ready rack server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD), AXIS S1132 provides high-performance and reliability for your system.

- > **Ease of installation**
- > **AXIS Camera Station licenses included**
- > **Full compatibility with Axis products**
- > **3-year hardware warranty with on-site replacement service**



AXIS S1132

Licenses	32 AXIS Camera Station core licenses included, can be upgraded up to 48 licenses (sold separately)	1x Serial port
Processor	Intel® Core i3-8100	Operating conditions
Memory	8 GB	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)
Storage	16 TB (4x4 TB) hot swappable Enterprise Class HDD, 7200 rpm 12 TB usable space after RAID Total HDD slots: 4 Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10	Storage conditions
Operating system	Microsoft® Windows® 10 Enterprise Operating system recovery: yes Operating system drive: 240 GB SSD	Approvals
Video streaming	Not intended for local viewing of video. Recommended to use AXIS desktop terminals.	EN/IEC/UL 60950-1, FCC part 15 class A, VCCI class A, RCM AS/NZS CISPR 32 Class A, EN 55032, class A, ICES-003/NMB-003 Class A, KC KN32 Class A, KN-35, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, NOM, BSMI, EAC
Recording	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.	Dimensions
Power	Up to 2 x 350 W hot-plug redundant power supplies (100 - 240 V AC, 50/60 Hz, 4.8 - 2.4 A)	596 x 484 x 43 mm (21.5 x 17.1 x 1.67 in), 1U chassis
Connectors	3x USB 2.0 2x Ethernet (RJ45) 1 GbE 1x VGA	Weight
		13.5 kg (29.7 lb)
		Included accessories
		Rack rails and power cords
		Optional accessories
		Axis desktop terminals For more accessories, see axis.com
		Warranty
		Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility